

# Touchscreen bank passbook printing kiosk with card reader, EPP, invoice printer and receipt thermal printer

## Bank passbook printing Kiosk


# A1

### Applications

- Bank pass book printing
- Ticket vending
- Insurance vending
- Credit card payment
- Utility bill collection
- Information ads

### Features

1. Powerful up-to-date CPU;
2. Waterproof IR/SAW touchscreen;
3. Zebra/CUSTOM branded printers;
4. DES EPP with motorized card reader;
5. Invoice dot-matrix printer;
6. Bank passbook printer and list printer
7. All steel sleek anti graffiti enclosure



Invoice printer  
Bank passbook printer



15 inch water-proof SAW touchscreen

Metal EPP

Receipt printer  
Motorized card reader

List printer

High performance host computer

Stereo audio

UPS



Component/function layouts

### Specifications

Model Name	A1B-Z17EL	A1C-M19
Processor	3.0GHz Intel® Core™ i5 2320	3.0GHz Intel® Pentium™ E6600(fan)
RAM	4Gb DDR II(16G max)	2Gb DDR II(4G max)
HDD	60G SSD or 500G 7200rpm 3.5" hard driver Up to 3TB size	
Monitor	17" LCD with DX9 decoding acceleration	19" LCD with DX9 decoding acceleration
Touchscreen	Water proof IR/SAW touchscreen	
Receipt printer	Zebra KR203	Zebra KR203
Invoice printer	STAR DP912	
Metal EPP	MKP2920	
Bank passbook printer	Nantian PR9	Nantian PR9
List printer	(None)	TTP8200
Motorized card reader	Rm6 hybrid card reader for IC, Magnetic and M1 cards	
3G/GPRS Modem(optional)	Simemse MC55/52 GPRS dual band SMS modem	
UPS	SANTAK K500 PRO UPS for at least 5 mins of power	
Audio	Bi-stereo channel 2X10W speakers	
Enclosure	Durable all-steel anti graffiti coating washable with agent Very low noise ventilation system, running noise<45dB Ergonomically sleek and smart design Easy to install and operate with drawers Security lock with crossbars Moistureproof,Antirust,Anti-acid,Static free Dimensions: 45-56cm * 45-66cm * 145-165cm	
Rear I/O Connectors	Power Jack Fuse(3A) Main power switch Host PC Power-on switch 1 COM 2 USB2.0 1 GbE LAN RJ45	
Fans	110 or 220 V AC selective Operation noise level: <45dB	
Power consumption	110V AC or 220V AC(with fans) 50-60Hz 3A	
Operating System	XP, WIN 7, WinCE, XPe, WES, Linux2.6, Ubuntu9, Fedora10	
Operating Temperature	0°C up to 45°C(need heater in below 0°C environment)	
Operating Humidity	0% ~ 95% (relative humidity; non-condensing)	

