

# Electricity payment collection touchscreen kiosk with bill validator, bank card reader, EPP and invoice printer


## Electricity payment touchscreen kiosk A5

### Applications

- Electricity bill payment
- Ticket vending
- Insurance vending
- Credit card payment
- Utility bill collection
- Information ads

### Features

1. Powerful up-to-date CPU;
2. Waterproof CA/IR/SAW touchscreen;
3. CUSTOM branded printers;
4. DES EPP with motorized card reader;
5. Invoice dot-matrix printer;
6. Universal bank notes acceptor
7. All steel sleek anti graffiti enclosure



- 17/15 inch water-proof SAW touchscreen
- Metal EPP
- Receipt printer
- Bank notes/bill validator
- High performance host computer
- UPS
- Stereo audio
- Motorized card reader
- Invoice printer



### Component/function layouts

### Specifications

Model Name	A5N17CCEL	A5C-MSC19
Processor	2.5GHz Intel® Core™ i3 2100T	3.1GHz Intel® XEON™ E3-1285L V3(fan)
RAM	2Gb DDR II(16G max)	4Gb DDR II(4G max)
HDD	60G SSD or 500G 7200rpm 3.5" hard driver Up to 3TB size	
Monitor	17" LCD with DX9 decoding acceleration	19" LCD with DX9 decoding acceleration
Touchscreen	Water proof CA/IR/SAW touchscreen	
Receipt printer	CUSTOM TG2480	CUSTOM TG2480
Invoice printer	STAR DP912	
Metal EPP	MKP2920	
Bill validator	CASHCODE SM	MEI SC83L
List printer	(None)	KM216
Motorized card reader	Rm6 hybrid card reader for IC, Magnetic and M1 cards	
3G/GPRS Modem(optional)	Simemse MC55/52 GPRS dual band SMS modem	
UPS	SANTAK K1000 PRO UPS for at least 15 mins of power	
Audio	Bi-stereo channel 2X3W speakers	
Enclosure	Durable all-steel anti graffiti coating washable with agent Very low noise ventilation system, running noise<45dB Ergonomically sleek and smart design Easy to install and operate with drawers Security lock with crossbars Moistureproof,Antitrust,Anti-acid,Static free Dimensions: 45-56cm * 45-66cm * 145-165cm	
Rear I/O Connectors	Power Jack Fuse(3A) Main power switch Host PC Power-on switch 1 COM 2 USB2.0 1 GbE LAN RJ45	
Fans	110 or 220 V AC selective Operation noise level: <45dB	
Power consumption	110V AC or 220V AC(with fans) 50-60Hz 3A	
Operating System	XP, WIN 7, WinCE, XPe, WES, Linux2.6/3.1, Ubuntu, Fedora	
Operating Temperature	0°C up to 45°C(need heater in below 0°C environment)	
Operating Humidity	0% ~ 95% (relative humidity; non-condensing)	

