

# Dual screen payment photo Kiosk APD16

## Applications

- Banking receipt printing
- Photo&card vending
- Insurance vending
- Credit card payment
- Utility bill collection
- Information ads

## Features

1. Powerful up-to-date CPU;
2. Waterproof CA/IR/SAW touchscreen;
3. Mitsubishi/CUSTOM branded printers;
4. metal keyboard&motorized card reader;
5. Dye-sublimation photo printer;
6. High quality Cash validator
7. All steel sleek anti graffiti enclosure



Stereo audio

Receipt printer

Photo printer

22/32/42 inch advertisement display

19/17/15 inch water-proof SAW touchscreen

Metal PINpad

Cash validator

Motorized card reader

High performance host computer

UPS



## Component/function layouts

## Specifications

Model Name	APD16B-C17NE	APD16C-M19
Processor	3.0GHz Intel® Core™ i5	3.2GHz Intel® Pentium™ G3430(fan)
RAM	4Gb DDR III(16G max)	4Gb DDR III(16G max)
HDD	60G SSD or 500G 7200rpm 3.5" hard driver Up to 3TB size	
Ads Monitor	22" LCD with DX9 LED backlighted	22" LCD with DX9 LED backlighted
Monitor	17" LCD with DX9 decoding acceleration	19" LCD with DX9 decoding acceleration
Touchscreen	Waterproof capacitive proof IR/SAW touchscreen	
Receipt printer	CUSTOM TG2480	CUSTOM TG2480
Photo printer	Mitsubishi CP9810DW-C	Mitsubishi CP9810DW-C
Metal keyboard	MKT2752	MKT2752
Cash validator	Cashcode MSM	MEI SCL83
Motorized card reader	Rm6 hybrid card reader for IC, Magnetic and M1 cards	
3G/GPRS Modem(optional)	Simemse MC55/52 GPRS dual band SMS modem	
UPS	SANTAK K1000 PRO UPS for at least 5 mins of power	
Audio	Bi-stereo channel 2X10W speakers	
Enclosure	Durable all-steel anti graffiti coating washable with agent Very low noise ventilation system, running noise<45dB Ergonomically sleek and smart design Easy to install and operate with drawers Security lock with crossbars Moistureproof,Antirust,Anti-acid,Static free Dimensions: 65-75cm * 65-80cm * 215-255cm	
Rear I/O Connectors	Power Jack Fuse(3A) Main power switch Host PC Power-on switch 1 COM(totally 4-6 COMs) 2 USB2.0(totally 8-12 USBs) 1 GbE LAN RJ45	
Fans	110 or 220 V AC selective Operation noise level: <45dB	
Power consumption	110V AC or 220V AC(with fans) 50-60Hz 3A	
Operating System	XP, WIN 7, WinCE, XPe, WES, Android, Linux2.6, Ubuntu9, Fedora10	
Operating Temperature	0°C up to 45°C(need heater in below 0°C environment)	
Operating Humidity	0% ~ 95% (relative humidity; non-condensing)	

