

Touchscreen digital signage

Digital Signage

D6

Applications

Museum
Exhibition
Apps store
Presentation
Information kiosk

Features

1. Dual Core Intel Core i3 2100;
2. Full HD touchscreen monitor;
3. Full view angle IPS display;
4. Multi touch optional
5. All steel anti-graffiti enclosure

Component/function layouts



46" FULL HD touchable IPS main monitor

All steel anti-graffiti enclosure stand



Specifications

Part Name	D5B-46DIDT
Processor	Intel Core i3 2100
RAM	4Gb DDR III(16G max)
HDD	60G SSD or 500G 7200rpm 3.5" hard driver Up to 3TB size
Display	46" LCD display with DID LED backlight(500 ~ 1500 nits)
Touchscreen	46" waterproof IR touchscreen
Rear I/O Connectors	Power Jack Fuse(3A) Power switch Host computer Power-on switch 1 COM 2 USB2.0 1 GbE LAN RJ45
Fans	110 or 220 V AC selective Operation noise level: <45dB
Power consumption	110V AC or 220V AC(with fans) 50-60Hz 3A
Operating System	WINDOWS XP/7/Linux 2.6 distribution(i.e. Fedora 9, CentOS 5, Ubuntu 10 and SUSE etc)
Operating Temperature	0°C up to 50°C(need heater in below 0°C environment)
Operating Humidity	0% ~ 95% (relative humidity; non-condensing)

CE FC

ROHS
COMPLIANT

