

Slim&sleek touchscreen kiosk with keyboard




Applications

- Internet browse
- Exhibition demonstration
- Entry registration
- Hotel check-in
- Information ads

Features

1. Powerful up-to-date CPU;
2. Waterproof IR/SAW touchscreen;
3. Cherry mechanic keyboard;
4. All steel sleek anti graffiti enclosure



GPRS modem for SMS(optional)

17/15 inch water-proof SAW touchscreen

custom LOGO area

Mechanic keyboard

Low noise fans with replaceable foam

High performance host computer

Stereo audio

UPS(optional)



Component/function layouts

Specifications

Model Name	K1B-K17N	K1E-15E
Processor	2.5GHz Intel® Core™ i3 2100	3.0GHz Intel® Pentium™ E6600(fan)
RAM	4Gb DDR II(16G max)	2Gb DDR II(4G max)
HDD	60G SSD or 500G 7200rpm 3.5" hard driver Up to 3TB size	
Monitor	17" LCD with DX9 decoding acceleration	15" LCD with DX9 decoding acceleration
Touchscreen	Water proof IR/SAW touchscreen	
Notebook keyboard	Mechanic keyboard with trackball(Cherry keyswitch)	
GPRS Modem	Simemse MC55 GPRS dual band SMS modem	
UPS	SANTAK K500 PRO UPS for at least 5 mins of power	
Audio	Bi-stereo channel 2X10W speakers	
Enclosure	Durable all-steel anti graffiti coating washable with agent Very low noise ventilation system, running noise<45dB Ergonomically sleek and smart design Easy to install and operate with drawers Security lock with crossbars Moistureproof,Antirust,Anti-acid,Static free Dimensions: 42-56cm * 45-66cm * 152-183cm	
Rear I/O Connectors	Power Jack Fuse(3A) Main power switch Host PC Power-on switch 1 COM 2 USB2.0 1 GbE LAN RJ45	
Fans	110 or 220 V AC selective Operation noise level: <45dB	
Power consumption	110V AC or 220V AC(with fans) 50-60Hz 3A	
Operating System	XP, WIN 7, WinCE, XPe, WES, Linux2.6, Ubuntu9, Fedora10	
Operating Temperature	0°C up to 45°C(need heater in below 0°C environment)	
Operating Humidity	0% ~ 95% (relative humidity; non-condensing)	

