

TD5 dualscreen 19+19 inch touchscreen payment kiosk with ticket printer, card printer&dispenser and payment card reader+EPP

Dualscreen touchscreen kiosk TD5

Applications

Advertisement
Ticket vending
Card dispenser
Card vending
Invoice

Features

1. Waterproof CA/IR/SAW touchscreen;
2. HD PIN hole camera
3. Invoice and receipt printer
4. Mobile on Desktop(MoDT) industrial computer
5. Card and ticket dispenser
6. All steel anti graffiti enclosure



19" advertisement display

HD PIN hole camera
Dual stereo audio

17/19 inch water-proof touchscreen

Card reader

Invoice printer

Movement sensor

UPS(internal)


Card dispenser

Industrial MoDT box IPC

Thermal printer

Metal EPP

Ticket printer



Component/function layouts

Specifications

Model Name	TD5B-199	TD5G-199
Processor	Intel® Core i3-2100T(fan)	Intel® XEON™ E3-1285Lv3(fan)
Chipset	Intel® H75	Intel® H81
RAM	4Gb DDR III(16Gmax)	4Gb DDR III(max)
HDD	5000G 7200rpm 3.5" hard driver Up to 3TB size	AMD series 120G 2.5" MSATA(MLC) Up to 3TB size
Monitor	19" LCD with DX11 decoding acceleration	19" LCD with DX11 decoding acceleration
Touchscreen	Water proof CA/IR/SAW touchscreen with function keys	
Advertisement display	19"(16:9) LCD display	19"(16:9) LCD display
HD camera	OV FC85	TSV 500P
Bank reader	ZK RM6	ZK RM6
Metal EPP	ZK MKP2910	ZK MKP2910
Thermal printer	SKT80T	CUSTOM TG280
Invoice printer	EPSON U220	EPSON U220
Ticket printer	CUSTOM VK80E	CUSTOM VK80E
Card printer&dispenser	Evolis Primacy high speed card printer and dispenser	
Wireless	WIFI/YUGE 920 4G module(optional)	
UPS	SANTAK K1000 PRO UPS for at least 15 mins of power	
Audio	Bi-stereo channel 2X5W speakers	
Enclosure	Durable all-steel anti graffiti coating washable with agent Very low noise ventilation system, running noise<45dB Ergonomically sleek and smart design Easy to install and operate with drawers Security lock with crossbars Moistureproof,Antirust,Anti-acid,Static free Dimensions: (package)680*750*2030mm; (machine)590x650x1730/1850mm	
Rear I/O Connectors	Power Jack Fuse(6A) Power switch 1 COM 2 USB2.0 1 GbE LAN RJ45	
Fans	110 or 220 V AC selective Operation noise level: <45dB	
Power consumption	110V AC or 220V AC(with fans) 50-60Hz 5A	
Operating System	XP, WIN 7, Android, WinCE, XPe, WES, Linux2.6, Ubuntu9, Fedora10	
Operating Temperature	0°C up to 50°C(need heater in below 0°C environment)	
Operating Humidity	0% ~ 95% (relative humidity; non-condensing)	

